

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

· **1.1 Product identifier**

· **Trade name:** BRUNOX® epoxy® - BULK

· **UFI:** WRGA-YVXS-7206-2WNT

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category**

PC9a Coatings and paints, thinners, paint removers

PC14 Metal surface treatment products

· **Process category**

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

· **Environmental release category**

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· **Application of the substance / the mixture** Coating material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

BRUNOX Korrosionsschutz GmbH

Adlzreiterstrasse 13, 85051 Ingolstadt

Postfach 100127 , 85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04

Fax + 49/ (0) 841 961 29 13

E-mail: office@brunox.com

UFI info / E-mail: ufi@brunox.com

www.brunox.de

·
BRUNOX AG

Tunnelstrasse 6

CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80

Fax +41/ (0)55 285 80 81

E-mail: office@brunox.com

www.brunox.swiss

UFI info / E-mail: ufi@brunox.com

(Contd. on page 2)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 1)

Further information obtainable from:

Abteilung Produktsicherheit / Product Safety Department:

Tel. - Switzerland: +41/ (0)55 285 80 80

Tel. - Germany: +49 / (0)841 961 29 04

Mo - Do / Mon - Thu: 08:00 - 16:00 Uhr

Fr / Fri: 08:00 - 12:00 Uhr

1.4 Emergency telephone number:

Toxikologisches Informationszentrum

CH - 8030 Zürich, Freiestrasse 16

Tel. +41/ 044 251 51 51

Notruf - CH, STIZ : 145

Notruf - BE - : 070 -245 245

Notruf - GB - : 844 892 0111

Notruf - IE - : + 353 1 837 9964 (medical professionals); + 353 1 809 2166 (public)

Notruf - IS - : + 354 543 22 22

Notruf - JP - : + 81 72 727 2499; + 81 29 852 9999

Notruf - NZ - : 0800 764 766

Notruf - PK - : + 92 21 9920509; + 92 21 35686535

Notruf - PH - : + 632 524 10 78; + 632 544 84 00; local 2311

Notruf - SA - : + 966 146 77 353, + 966 3 8155 646; Ext. 280, 282, 283

Notruf - TH - : + 66 201 1086

Notruf - UAE - : 800 424

Notruf - ZA - : + 27 824 910 160

Notruf - D - : Giftnotrufzentrale 030 19240

EUROPÄISCHE NOTRUFNR. : 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture**Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 2)

· Hazard pictograms

GHS02 GHS07

· Signal word Danger**· Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 108-65-6

2-methoxy-1-methylethyl acetate

10-25%

EINECS: 203-603-9

⚠ Flam. Liq. 3, H226

Index number: 607-195-00-7

Reg.nr.: 01-2119475791-29-

XXXX

(Contd. on page 4)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

CAS: 67-63-0
EINECS: 200-661-7
Index number: 603-117-00-0
Reg.nr.: 01-2119457558-25-XXXX

propan-2-ol
⚠ Flam. Liq. 2, H225
⚠ Eye Irrit. 2, H319; STOT SE 3, H336

(Contd. of page 3)
≥2.5-<10%

CAS: 67-64-1
EINECS: 200-662-2
Index number: 606-001-00-8
Reg.nr.: 01-2119471330-49-XXXX

acetone
⚠ Flam. Liq. 2, H225
⚠ Eye Irrit. 2, H319; STOT SE 3, H336
EUH066

≥2.5-<10%

CAS: 107-98-2
EINECS: 203-539-1
Index number: 603-064-00-3
Reg.nr.: 01-2119457435-35-XXXX

1-methoxy-2-propanol
⚠ Flam. Liq. 3, H226
⚠ STOT SE 3, H336

2.5-10%

CAS: 64-18-6
EINECS: 200-579-1
Index number: 607-001-00-0
Reg.nr.: 01-2119491174-37-XXXX

formic acid
⚠ Acute Tox. 3, H331
⚠ Skin Corr. 1C, H314
⚠ Acute Tox. 4, H302
Specific concentration limits:
Skin Corr. 1A; H314: $C \geq 90 \%$
Skin Corr. 1B; H314: $10 \% \leq C < 90 \%$
Skin Irrit. 2; H315: $2 \% \leq C < 10 \%$
Eye Irrit. 2; H319: $2 \% \leq C < 10 \%$

≥2.5-<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Take affected persons out into the fresh air.
Do not leave affected persons unattended.
Position and transport stably in side position.
Seek medical treatment.

· **After inhalation:**

Take affected persons into fresh air and keep quiet.
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
A person vomiting while laying on their back should be turned onto their side.

(Contd. on page 5)
EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 4)

- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

(Contd. on page 6)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 5)

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

· Information about storage in one common storage facility: Store away from foodstuffs.**· Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Storage class: 3**· 7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:****CAS: 108-65-6 2-methoxy-1-methylethyl acetate**IOELV Short-term value: 550 mg/m³, 100 ppmLong-term value: 275 mg/m³, 50 ppm

Skin

CAS: 67-64-1 acetoneIOELV Long-term value: 1210 mg/m³, 500 ppm**CAS: 107-98-2 1-methoxy-2-propanol**IOELV Short-term value: 568 mg/m³, 150 ppmLong-term value: 375 mg/m³, 100 ppm

Skin

CAS: 64-18-6 formic acidIOELV Long-term value: 9 mg/m³, 5 ppm**· Additional information:** The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Appropriate engineering controls** No further data; see section 7.**· Individual protection measures, such as personal protective equipment****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 7)

EU

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 6)

Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:

Filter A/P2

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Check the permeability prior to each renewed use of the glove.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed goggles

· Body protection: Solvent resistant protective clothing

*

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information****· Colour:**

Amber coloured

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

(Contd. on page 8)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 7)

· <u>Boiling point or initial boiling point and boiling range</u>	82 °C
· <u>Flammability</u>	Not applicable.
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	1.5 Vol %
· <u>Upper:</u>	20 Vol %
· <u>Flash point:</u>	13 °C
· <u>Auto-ignition temperature:</u>	225 °C
· <u>Decomposition temperature:</u>	Not determined.
· <u>pH at 20 °C</u>	3.9
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined.
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Partition coefficient n-octanol/water (log value)</u>	Not determined.
· <u>Vapour pressure at 20 °C:</u>	12 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.99 g/cm ³
· <u>Relative density</u>	Not determined.
· <u>Vapour density</u>	Not determined.
· <u>9.2 Other information</u>	
· <u>Appearance:</u>	
· <u>Form:</u>	Fluid
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Water:</u>	27.25 %
· <u>VOC (EC)</u>	40.86 %
· <u>Solids content:</u>	1.5 %
· <u>Change in condition</u>	
· <u>Evaporation rate</u>	Not determined.
· <u>Information with regard to physical hazard classes</u>	
· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Highly flammable liquid and vapour.
· <u>Flammable solids</u>	Void

(Contd. on page 9)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 8)

· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Forms explosive gas mixture with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.
- **Additional information:**
As long as the prescribed application concentrations are maintained there is no danger that stable emulsions will form.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
ATE (Acute Toxicity Estimates)
Oral LD50 36,789 mg/kg (rat)
Inhalative LC50/4 h 100 mg/l

CAS: 108-65-6 2-methoxy-1-methylethyl acetate
Oral LD50 8,532 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rat)
Inhalative LC50/4 h 35.7 mg/l (rat)

CAS: 67-63-0 propan-2-ol
Oral LD50 5,045 mg/kg (rat)
Dermal LD50 12,800 mg/kg (rabbit)

(Contd. on page 10)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 9)

Inhalative LC50/4 h 30 mg/l (rat)

CAS: 67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 >15,800 mg/kg (rat)
20,000 mg/kg (rabbit)

Inhalative LC50/4 h 76 mg/l (rat)

CAS: 107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

CAS: 64-18-6 formic acid

Oral LD50 1,100 mg/kg (rat)

Inhalative LC50/4 h 3 mg/l (ATE)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**· Germ cell mutagenicity** Based on available data, the classification criteria are not met.**· Carcinogenicity** Based on available data, the classification criteria are not met.**· Reproductive toxicity** Based on available data, the classification criteria are not met.**· STOT-single exposure** Based on available data, the classification criteria are not met.**· STOT-repeated exposure** Based on available data, the classification criteria are not met.**· Aspiration hazard** Based on available data, the classification criteria are not met.**· 11.2 Information on other hazards****· Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity**· Aquatic toxicity:****CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

EC50 >500 mg/kg (daphnia)

LC50/96 h 160 mg/l (pimephales promelas)

CAS: 67-64-1 acetone

LC50/48 h 8,800 mg/l (daphnia)

CAS: 107-98-2 1-methoxy-2-propanol

EC50 >500 mg/kg (daphnia)

LC50/96 h 4,600-10,000 mg/l (leuciscus idus)

(Contd. on page 11)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 10)

CAS: 64-18-6 formic acid

EC50 120 mg/kg (daphnia)

LC50/48 h 122 mg/l (leuciscus idus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
HP3 Flammable
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR/RID/ADN, IMDG, IATA** UN1866
- **14.2 UN proper shipping name**
- **ADR/RID/ADN** 1866 RESIN SOLUTION, special provision 640D
- **IMDG, IATA** RESIN SOLUTION

(Contd. on page 12)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 11)

· 14.3 Transport hazard class(es)**· ADR/RID/ADN, IMDG, IATA****· Class**

3 Flammable liquids.

· Label

3

· 14.4 Packing group**· ADR/RID/ADN, IMDG, IATA**

II

· 14.5 Environmental hazards:**· Marine pollutant:**

No

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code):

33

· EMS Number:

F-E, S-E

· Stowage Category

B

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:**· ADR/RID/ADN****· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

D/E

· IMDG**· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, II

*

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 13)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 12)

- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
None of the ingredients is listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
CAS: 67-64-1 acetone
- **Regulation (EC) No 273/2004 on drug precursors**
CAS: 67-64-1 acetone 3
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
CAS: 67-64-1 acetone 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H336 May cause drowsiness or dizziness.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- **Date of previous version:** 16.02.2024
- **Version number of previous version:** 14
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 14)

EU



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2024

Version number 15 (replaces version 14)

Revision: 20.02.2024

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 13)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

EU